

suprabeam®

Q2_{xr}

Protected Internal
USB-C Charging

Extremely efficient DC converter
technology for longer runtimes



800 LUMENS



Li-Po
1100 mAh



175 m



67 g



10° - 70°

502.6011

PACKAGING



Customs Tariff Number:	8513 1000
Packaging:	Recyclable Cardboard Packaging
Single Box Content / Size / Weight:	1 pcs, height/width/depth: 18 x 6 x 3 cm / 152 g
Master Box Content / Size / Weight:	36 pcs, height/width/depth: 20.5 x 20 x 38.5 cm / 6 kg
Part. No.:	502.6011
EAN-CODE:	5704049909151

SPECIFICATIONS

LED / Focus Configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Prime Aluminium quality 6061, anodized
Case Color:	Anthracite Dark Grey
Switch at Rear:	Electronic Switch with Solid Silicone Button
Dimensions:	L: 118 mm, ø: 26 mm
Weight incl. Battery:	67 g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature (Operation):	-20°C to +50°C

ELECTRONICS

Built in Controller:	Yes, DIM and STEP mode
Standard Power Source:	1 x Li-Po (1100 mAh)
Charging Time:	80% = 1 h 45 min, 100% = 2 h 40 min
Beam / Distance:	Variable from Spot to Floodlight / 175 Meters
Luminous Flux:	Max: 800 lm / Dim: 250-6 lm
Lighting Time:	Max: 1 h 30 min / Low dim: 120 h
Accessories Included:	USB-C-Cable
Charging Temperature:	-0°C to +45°C

Distributor's Stamp:

Suprabeam is manufactured by
the Steiner Group and distributed
worldwide by:

Suprabeam A/S
Dyssen 3
DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212
www.suprabeam.com
info@suprabeam.com