

2000 LUMENS



Li-ion 3000 mAh



360 m



182 g



10° - 70°

PACKAGING



Customs Tariff Number:	8513 1000
Packaging:	Recyclable Cardboard Packaging
Single Box Content / Size / Weight:	1 pcs, height/width/depth: 19 x 19 x 5 cm / 472 g
Master Box Content / Size / Weight:	5 pcs, height/width/depth: 22 x 28 x 21 cm / 2.6 kg
Part. No.:	505.7111
EAN-CODE:	5704049911482

SPECIFICATIONS

LED / Focus Configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Prime Aluminium quality 6061, anodized
Case Color:	Black
Switch at Rear:	Electronic Switch with Solid Silicone Button
Dimensions:	L: 161 mm, ø: 39 mm
Weight incl. Battery:	182 g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature (Operation):	-20°C to +50°C

ELECTRONICS

Built in Controller:	Yes, DIM and STEP mode
Standard Power Source:	Li-ion 18650 (3000 mAh)
Charging Time:	80% = 2 h, 100% = 3 h 40 min
Beam / Distance:	Variable from Spot to Floodlight / 360 Meters
Luminous Flux:	Max: 2000 lm / Medium: 400 lm / Low: 50 lm / Dimming: 800 - 6 lm / Strobe 10 Hz
Lighting Time:	Max: 1 h 15 min / Medium: 3 h 30 min / Low: 28 h / Dimming: 1h 30 min - 118 h
Accessories Included:	Holster, Strap, Anti-Roll Ring, USB-C Cable, Wall Charger
Charging Temperature:	-0°C to +45°C

Distributor's Stamp:

Suprabeam is manufactured by the Steiner Group and distributed worldwide by:

Suprabeam A/S Dyssen 3 DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212 **www.suprabeam.com** info@suprabeam.com