

Danish | Swiss

 suprabeam[®]

Q3



**500
LUMENS**



**99 G
WEIGHT**



3XAAA



**10°-70°
BEAM ANGLE**



**DIM
FUNCTION**



Sliding Hyperfocus™



Electronic Switch



Practical Pouch



Traffic Wand (Sold separately)
950.095



IPX4
WATER RESISTANT



DIMMING

°K

5000
KELVIN



70
CRI






10° - 70°
BEAM ANGLE



230 M
LIGHT DISTANCE

LIGHT DATA



	 LUMENS	 RUNTIME HOURS:MIN	 DISTANCE METERS
MAX	500	3:30	230
DIMMING	500-10	3:30-75	230-32
DIMMING-250 LM	250	4:30	163

Suprabeam data are all based on the ANSI FL1 standard

SPECIFICATIONS

Material:	Prime Aluminium quality 6061, anodized
Dimensions:	L: 113.5 mm, ø: 26.5 mm
Operating Temperature:	-20° C - +50° C
Customs Tariff Number:	8513 1000
Single Box Content / Size / Weight	1 pcs, height/width/depth: 17.5 x 12 x 3 cm / 215 g
Master Box Content / Size / Weight	18 pcs, height/width/depth: 20.2 x 19.5 x 37.5 cm / 4.1 kg
Part. No.:	503.1111
EAN:	5704049908253

CONTENT



Suprabeam A/S
Dyssen 3
DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212
www.suprabeam.com
info@suprabeam.com