

# suprabeam®

## Q4

Stepless power adjustment from  
400 to 8 lumens

Efficient performance  
from 3 x AAA batteries

Versatile use with  
Sliding Hyperfocus™



# 400 LUMENS



3 x AAA



200 m



152 g



10° - 70°

504.1011

# PACKAGING



<b>Customs Tariff Number:</b>	8513 1000
<b>Packaging:</b>	Recyclable Cardboard Packaging
<b>Single Box Content / Size / Weight:</b>	1 pcs, height/width/depth: 20 x 15 x 6 cm / 367 g
<b>Master Box Content / Size / Weight:</b>	12 pcs, height/width/depth: 22.7 x 31.5 x 37.5 cm / 4.9 kg
<b>Part. No.:</b>	504.1011
<b>EAN-CODE:</b>	5704049908284

# SPECIFICATIONS

<b>LED / Focus Configuration:</b>	1 CREE Power Chip / Sliding Hyperfocus™
<b>Case Material / Surface Treatment:</b>	Prime Aluminium quality 6061, anodized
<b>Case Color:</b>	Anthracite Dark Grey
<b>Switch at Rear:</b>	Electronic Switch with Solid Silicone Button
<b>Dimensions:</b>	L: 129 mm, ø: 36 mm
<b>Weight incl. Battery:</b>	152 g
<b>Ingress Protection Rating:</b>	Splash Waterproof IPx4
<b>Temperature (Operation):</b>	-20°C to +50°C

# ELECTRONICS

<b>Built in Controller:</b>	Yes, dimmable
<b>Standard Power Source:</b>	3 x AAA Alkaline
<b>Compatible with rechargeable cells:</b>	Yes, with AAA NiMh 1.2V
<b>Beam / Distance:</b>	Variable from Spot to Floodlight / 200 Meters
<b>Luminous Flux:</b>	Max: 400 lm / Dim: 400-8 lm
<b>Lighting Time:</b>	Max: 2 h / Low dim: 80 h
<b>Accessories Included:</b>	Pouch with Nylon Fastener and Press Stud, Strap
<b>Charging Temperature:</b>	-0°C to +45°C

Distributor's Stamp:

Suprabeam is manufactured by  
the Steiner Group and distributed  
worldwide by:

Suprabeam A/S  
Dyssen 3  
DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212  
**www.suprabeam.com**  
info@suprabeam.com