Suprabeam®

defend

Tactical tail cap to break light surfaces

Stepless power adjustment from 400 to 8 lumens

Versatile use with Sliding Hyperfocus™



Anti-Roll Ring

400 LUMENS



🔊 suprabeam[®] 📭







3 x AAA 200 m

152 g

10° - 70°

PACKAGING



Customs Tariff Number:	8513 1000
Packaging:	Recyclable Cardboard Packaging
Single Box Content / Size / Weight:	1 pcs, height/width/depth: 20 x 15 x 6 cm / 381 g
Master Box Content / Size / Weight:	12 pcs, height/width/depth: 22.7 x 31.5 x 37.5 cm / 5.1 kg
Part. No.:	504.4011
EAN-CODE:	5704049908291

SPECIFICATIONS

LED / Focus Configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Prime Aluminium quality 6061, anodized
Case Color:	Black
Switch at Rear:	Electronic Switch with Solid Silicone Button
Dimensions:	L: 129 mm, ø: 36 mm
Weight incl. Battery:	152 g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature (Operation):	-20°C to +50°C

ELECTRONICS

Built in Controller:	Yes, dimmable
Standard Power Source:	3 x AAA Alkaline
Compatible with rechargeable cells:	Yes, with AAA NiMh 1.2V
Beam / Distance:	Variable from Spot to Floodlight / 200 Meters
Luminous Flux:	Max: 400 lm / Dim: 400-8 lm
Lighting Time:	Max: 2 h / Low dim: 80 h
Accessories Included:	Pro. Tactical Pouch with Nylon Fastener and Press Stud, Strap, Anti-Roll Ring
Charging Temperature:	-0°C to +45°C

Distributor's Stamp:

Suprabeam is manufactured by the Steiner Group and distributed worldwide by:

Suprabeam A/S Dyssen 3 DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212 **www.suprabeam.com** info@suprabeam.com