

You might also like...

Q1



V3^{pro}
Rechargeable



Product Overview

Thank you for purchasing our Suprabeam Q7.

Equipped with the latest HighPower-Chip, current control electronics and combined with our Hyperfocus™ system Q7 offers impressive light output.

We do our best to make the products meet our high standards.


Should you unexpectedly encounter problems with the product, please contact your local Suprabeam dealer.

Register your product at www.suprabeam.com and get the latest information and news by e-mail

Mistakes and printing errors excepted

We highly recommend using Premium type batteries only to ensure high quality light output and long lighting time. We can not guarantee the light data if using battery types of lower quality

To protect the environment, this product is compatible with rechargeable batteries 1.2-1.5V (not Li-Ion 3.7V)



Steiner A/S
P.O. Pedersens Vej 14A · DK-8200 Aarhus N
Phone: +45 87 52 52 12
Fax: +45 87 52 52 15

Contact: info@suprabeam.com · www.suprabeam.com

Warranty and Warnings



 suprabeam®



Q7



Changing Battery




Operating

1x=	BOOST:	280 LM
2x=	High:	150 LM
3x=	Medium:	50 LM
4x=	Strobe:	10 Hz




Sliding Hyperfocus™




Manual

FOR MORE INFO:



www.suprabeam.com

Q7



Hours:	< 8 h
Battery:	2 x C Alcaline or NiMh
Beam angle:	Variable_Spot 5°_Flood 70°
Beam Distance:	215 m
Case Material	Anodized Aluminium
Weight:	322 g (incl. batteries)
Temp.	-20°C to + 50°C
IP Rating	x4
LED Type:	1 CREE LED Chip

Electronic Control:

BOOST:	280 Lumens
High:	150 Lumens
Low:	50 Lumens
Strobe:	10 Hz

Technical Data