

LED / Focus configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment	Anodized, High Strength Aluminium
Case Color:	Anthracite Dark Grey
Switch: Qual	ty Tested Switch At Rear - Constant / Momentary Light / Reduced Light
Dimensions:	L: 146mm, ø: 39mm
Weight incl. battery:	241g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperture:	-20°C to +50°C
Built in DC/DC Controller:	YES
Standard Power Source:	Li-ion 26650 (14.8 Wh)
Beam / Distance:	Variable from Spot to Floodlight / < 225 Meters
Luminous Flux: B	DOST: 300 Lumens / High: 200 Lumens / Low: 50 Lumens / Strobe 10 Hz
Lighting Time:	< 20 hours
Accessories included:	Pro. Quality Pouch with Velcro and Press Stud, Strap,
	100-240VAC Adaptor with USB cable and external ICR 26650 Charger
EAN-Code:	57 04049 90018 9 / 57 04049 90019 6 (additional battery)
Customs Tariff Number:	8513 1000
Packaging:	PE Portable Box with Space for Second Battery
Single Box Content / Size / Weight	: 1 pcs, 27.5 x 20.7 x 6.8 cm / 1.14 kg
Sales Box Content / Size / Weight:	6 pcs, 43.5 x 30.5 x 23 cm / 7.5 kg
Master Box Content / Size / Weigh	t: 6 pcs, 44.5 x 31 x 26.5 cm / 7.9 kg
Order's Adress:	sales@steinerweb.com
Part. No.:	900.075 / 900.076 (additional battery)

