

# suprabeam®

## M6<sub>xr</sub>

Proactive Safety Sensor  
Protecting Against Heat Damage

Exchangeable Battery  
With Integrated USB-C  
Charging



Powerful Integrated  
Magnet

Multi functional  
- Universal Torch and  
Headlamp in One

# 2000 LUMENS



Li-Ion  
3000 mAh



165 m



114 g



30°/70°

526.6111

# PACKAGING



<b>Customs Tariff Number:</b>	8513 1000
<b>Packaging:</b>	Recyclable Cardboard Packaging
<b>Single Box Content / Size / Weight:</b>	1 pcs, height/width/depth: 18 x 14 x 4 cm / 300 g
<b>Master Box Content / Size / Weight:</b>	10 pcs, height/width/depth: 37.5 x 19.5 x 20.2 cm / 3.4 kg
<b>Part. No.:</b>	526.6111
<b>EAN-CODE:</b>	5704049911628

# SPECIFICATIONS

<b>LED / Focus Configuration:</b>	1 CREE Power Chip
<b>Case Material / Surface Treatment:</b>	Prime Aluminium quality 6061, anodized
<b>Case Color:</b>	Black / Anthracite Dark Grey
<b>Switch at Rear:</b>	Electronic Switch with Solid Silicone Button
<b>Headband:</b>	Black fabric with silicone stripes, Fits to 50-70 centimeters
<b>Dimensions:</b>	L: 110 mm, ø (Tube): 23 mm, (Head): 32 mm
<b>Weight incl. Battery:</b>	114 g
<b>Ingress Protection Rating:</b>	Waterproof (2m) and Dust proof IP68
<b>Temperature (Operation):</b>	-20°C to +50°C (CR123: -40°C to +50°C)

# ELECTRONICS

<b>Built in Controller:</b>	Yes, dimmable
<b>Standard Power Source:</b>	Li-ion 18650 (3000 mAh), Compatible with CR123
<b>Charging Time:</b>	80% = 5 h 20 min, 100% = 4 h 10 min
<b>Beam / Distance:</b>	Mixed beam 20°/60° / 165 Meter
<b>Luminous Flux:</b>	Max: 2000 lm / Dimming: 600-6 lm / CR123 Max: 1500 lm
<b>Lighting Time:</b>	Max: 2 h 30 min, Dimming: 2 h 45 min - 260 h, CR123 Max: 2h
<b>Accessories Included:</b>	Washable Headband, USB-C Charging Cable, Adhesive Helmet Adapter, Strap, Manual
<b>Charging Temperature:</b>	-0°C to +45°C

Distributor's Stamp:

Suprabeam is manufactured by  
the Steiner Group and distributed  
worldwide by:

Suprabeam A/S  
Dyssen 3  
DK-8200 Aarhus N, Denmark

Phone: +45 87 525 212  
**www.suprabeam.com**  
info@suprabeam.com